

ABC STORED PRESSURE

Capacity : 1kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 8 - 12 sec.
- Range: 2Mtr.
- Rating: 1A - 8B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

Capacity : 2kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 8 - 12 sec.
- Range: 2Mtr.
- Rating: 1A - 8B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

Capacity : 4kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 2A - 21B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

Capacity : 6kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 3A - 34B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683



Capacity : 9kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 5Mtr.
- Rating: 4A - 55B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

BC DRY POWDER STORED PRESSURE

Capacity : 4kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 34B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



Capacity : 6kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 55B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



Capacity : 9kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 6Mtr.
- Rating: 89B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



MECHANICAL FOAM (CATRIDGE TYPE)

Capacity : 9 Ltr.

- Temperature Range: +5°C To + 55°C
- Discharge 90% & Duration: 25 - 60 sec.
- Range: 5Mtr.
- Rating: 4A - 55B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Refillable at site
- Safety Valve
- Brass Forged Cap
- CO2 Gas Propellant
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



MECHANICAL FOAM (STORED PRESSURE TYPE)

Capacity : 9 Ltr.

- Temperature Range: +5°C To + 55°C
- Discharge 90% & Duration: 25 - 60 sec.
- Range: 5Mtr.
- Rating: 4A - 55B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



WATER CO₂ (CARTRIDGE TYPE)

Capacity : 9 Ltr.

- Temperature Range: +5°C To + 55°C
- Discharge 95% & Duration: 25 - 60 sec.
- Range: 5Mtr.
- Rating: 4A

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Co₂ Gas Propellant
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



WATER CO₂ (STORED PRESSURE TYPE)

Capacity : 9 Ltr.

- Temperature Range: +5°C To + 55°C
- Discharge 95% & Duration: 25 - 60 sec.
- Range: 5Mtr.
- Rating: 4A

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



BC DRY POWDER CARTRIDGE TYPE

Capacity : 4kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 34B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Propellant: Co₂ Gas
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



Capacity : 6kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 55B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Propellant: Co₂ Gas
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



Capacity : 9kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 25 - 30 sec.
- Range: 6Mtr.
- Rating: 89B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Propellant: Co₂ Gas
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



CLEAN AGENT (STORED PRESSURE TYPE)



Capacity : 2kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 8 - 12 sec.
- Range: 2Mtr.
- Rating: 1A - 8B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



Capacity : 4kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 2A - 21B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 15683



Capacity : 6kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 3A - 34B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Design as per IS: 15683

ABC / CLEAN AGENT (MOUDLAR TYPE)



FEATURES & PERFORMANCE

Capacity	2 kgs.	5 kgs.	10 kgs.	15 kgs.
Working Pressure in kgs / cm2	7 to 15	7 to 15	7 to 15	7 to 15
Propellant	Nitrogen	Nitrogen	Nitrogen	Nitrogen
Area Protection in m2	1 - 1.5	3.5 - 4	7 - 8	8 - 10
Hanging vertically above risk	1.5 m	1.5 - 2m	1.75 - 2.3m	2-3m
Operation time in second	8 - 10	10 - 15	15 - 20	18 - 23

CO2 TYPE FIRE EXTINGUISHERS



Capacity : 2 kg. & 3 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 95% & Duration: 8 - 16 sec.
- Range: 2Mtr.
- Rating: 8B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Safety Valve
- Co2 Gas Propellant
- Design as per IS: 15683



Capacity : 4.5 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 95% & Duration: 8 - 16 sec.
- Range: 2.5 Mtr.
- Rating: 21B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Safety Valve
- Co2 Gas Propellant
- Design as per IS: 15683

TROLLEY MOUNTED CO2 TYPE FIRE EXTINGUISHERS



Capacity : 6.5 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 95%
- Duration: 8 - 18 sec.

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Safety Valve
- Co2 Gas Propellant
- Design as per IS: 2878



Capacity : 9 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 95%
- Duration: 8 - 30 sec.

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Safety Valve
- Co2 Gas Propellant
- Design as per IS: 2878



Capacity : 22.5 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 95%
- Duration: 12 - 30 sec.

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Safety Valve
- Co2 Gas Propellant
- Design as per IS: 2878

HIGHER CAPACITY

Capacity : 25 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 25 - 30 sec.
- Range: 6 Mtr.
- Propellant: Co2 Gas
- Powder: Soda bi Carb.

PERFORMANCE & FEATURES

- Co2 Regulator Valve Operated
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 10658



Capacity : 50 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 40 - 60 sec.
- Range: 8 Mtr.
- Propellant: Co2 Gas
- Powder: Soda bi Carb.

PERFORMANCE & FEATURES

- Co2 Regulator Valve Operated
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 10658



Capacity : 75 kg.

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 50 - 60 sec.
- Range: 10 Mtr.
- Propellant: Co2 Gas
- Powder: Soda bi Carb.

PERFORMANCE & FEATURES

- Co2 Regulator Valve Operated
- Refillable at site
- Safety Valve
- Brass Forged Cap
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 10658



WATER Co2

Capacity : 50 Ltr.

- Temperature Range: +5°C To + 55°C
- Discharge 90% & Duration: 60 - 180 sec.
- Range: 10 Mtr.
- Propellant: Co2 Gas
- AFFF: 6%

PERFORMANCE & FEATURES

- Co2 Cartige
- Refillable at site
- Brass Forged Cap
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 13385



MECHANICAL FOAM

Capacity : 50 Ltr.

- Temperature Range: +5°C To + 55°C
- Discharge 90% & Duration: 60 - 180 sec.
- Range: 10 Mtr.
- Propellant: Co2 Gas Cartridge

PERFORMANCE & FEATURES

- Co2 Cartige
- Refillable at site
- Brass Forged Cap
- Weather Resistance Epoxy
- Polyester base powder Coating
- Design as per IS: 13386



M.G. CABLE INDUSTRIES

Manufacturers : GI Cable Trays & All Earthing Materials

3/5, Ground Floor, Takwadi, Opp Yevale Tea Centre, Kalbadevi Road, Mumbai-400002. • Tel.: +91 22 4973 3629, 4913 7629
Cell : +91 96995 47310 • Email : mgcables29@gmail.com / info@mgcables.com • Website : www.mgcables.com

Authorised Stockist :

